

QUICK REF BELT DRIVE

MODEL	Capacity in MS mm	Spindle	Stroke mm	Throat mm	Motor kW	No of speeds	Speed range rpm	Power feed	Column dia mm	Table size mm	Max spindle to table mm	Max spindle to base mm	Weight kg
TB 4 STW	4	Chuck	40	180	0.9	Var E	1500-10000		50	n/a	n/a	275	20
TB 6 STW	6	Chuck	40	180	0.9	Var E	1250-8000		50	n/a	n/a	275	20
TB 8 STW	8	Chuck	40	180	0.9	Var E	1000-6500		50	n/a	n/a	275	20
TB 10 STW	10	Chuck	50	180	0.9	Var E	500-3000		50	n/a	n/a	275	20
TB 13 STW	13	Chuck	60	185	1.1	Var E	400-4500		60	n/a	n/a	360	55
Compact	13	Chuck	100	193	0.25	5	500/4000		70	295 x 235	1077	1258	61
LF 1	18	2 MT	75	185	0.45	5	400/3600		70	300 x 390	330	n/a	133
SB M 1 ST	18	2 MT	75	185	0.75	Var	300-3300		70	240 x 290	740	n/a	140
SB P 18 ST	18	2 MT	75	185	0.75	Var	300-3300		70	240 x 290	740	n/a	140
TB P 18 STE	18	2 MT	70	185	1.3	Var E	400-7000		70	240 x 290	330	n/a	85
KL-18	18	3 MT	120	250	0.55	10	200/4000		100	300 x 270	640	1210	175
LF 2	23	2 MT	75	185	0.75	10	200/3600		70	300 x 390	330	n/a	140
SB M 2 ST	23	2 MT	100	240	0.8	Var	250-4000		82	340 x 280	880	n/a	205
SB P 23 ST	23	2 MT	100	240	0.8	Var	250-4000		82	340 x 280	880	n/a	205
SB E 3	25	3 MT	90	240	0.8	12	250/4000		82	340 x 280	880	n/a	205
KL-25	25	3 MT	120	250	0.8	10	200/4000		100	300 x 270	640	1210	175
SB E 4	30	3 MT	125	260	1.3	12	125/2500		110	420 x 340	820	n/a	255
SB M 3 ST (MV)	30	3 MT	125	260	1.45	Var	125-4000	(Y)	110	420 x 340	790	n/a	275
SB P 30 ST (PV)	30	3 MT	125	260	1.45	Var	125-4000	(Y)	110	420 x 340	790	n/a	275
SZ-32	32	3 MT	150	300	1.3	10	145/1720		125	480 x 400	835	1285	270
AZ-32V	32	3 MT	150	300	1.3	Var	80-1170	Y	125	480 x 400	835	1285	290
SB E 5	35	3 MT	125	300	1.5	12	80/1600		125	590 x 450	820	n/a	255
SB M 4 ST (MV)	35	3 MT	125	280	2	Var	125-2000	(Y)	110	420 x 340	790	n/a	275
SB P 35 ST (PV)	35	3 MT	125	280	2	Var	125-2000	(Y)	110	420 x 340	790	n/a	275
SZ-34	35	4 MT	150	300	2.2	Var	100-2000		125	480 x 400	725	1230	360
AZ / BZ-34	35	4 MT	150	300	2.2	Var	100-2000	Y	125	480 x 400	725	1230	360
SB M 5 ST (MV)	40	4 MT	160	300	3	Var	100-2000	(Y)	125	590 x 450	700	n/a	420
SB P 40 ST (PV)	40	4 MT	160	300	3	Var	100-2000	(Y)	125	590 x 450	700	n/a	420
SZ-40	40	4 MT	180	350	3	Var	100-2000		150	560 x 480	690	1230	460
AZ / BZ-40	40	4 MT	180	350	3	Var	100-2000	Y	150	560 x 480	690	1230	460
BC-40V	40	4 MT	200	385	3	Var	60-200	Y	180	560 x 480	690	1170	660
BC-40VE	40	4 MT	200	385	3	Var E	30-230	Y	180	560 x 480	690	1170	670
BC-50V	50	4 MT	200	370	4	Var	60-200	Y	200	620 x 520	660	1245	760

QUICK REF

ALL-GEARED

MODEL	Capacity		Stroke mm	Throat mm	Motor kW	No of speeds	Speed range rpm	Power feed	Column dia mm	Table size mm	Max spindle to table mm	Max spindle to base mm	Weight kg
	in MS	mm Spindle											
TL-18	18	3 MT	120	250	0.8	8	75/2800		100	300 x 270	640	1210	185
TL-25	25	3 MT	120	250	1.1	8	75/2800		100	300 x 270	640	1210	185
S-25 (M)	25	3 MT	135	255	0.9	8	105/2900	(Y)	100	350 x 500	905	1195	180
S-28 (M)	32	3 MT	150	320	1.2	8	75/3010	(Y)	105	400 x 500	890	1235	235
SX-32	32	3 MT	150	300	0.75	9	104/1450		125	480 x 400	810	1280	315
AX-32	32	3 MT	150	300	1.1	9	104/1450	Y	125	480 x 400	810	1280	335
SX-34	35	4 MT	150	300	1.5	9	132/1852		125	480 x 400	725	1230	400
AX / BX-34	35	4 MT	150	300	1.5	9	132/1852	Y	125	480 x 400	725	1230	400
A / B-35	35	4 MT	200	370	1.5	9	81/1274	Y	160	560 x 480	780	1200	490
S-35 M/ME	35	4 MT	150	320	2	8	75/3010	Y	127	400 x 500	820	1150	290
S-40 (M/ME)	40	4 MT	190	330	2.2	8	90/1500	(Y)	140	400 x 500	820	1210	310
SX-40	40	4 MT	180	350	2.2	9	132/1852		150	560 x 480	690	1230	490
AX / BX-40	40	4 MT	180	350	2.2	9	132/1852	Y	150	560 x 480	690	1230	490
A / B-40	40	4 MT	200	385	2.2	9	61/1169	Y	180	560 x 480	780	1260	610
BP-40	40	4 MT	200	400	2.2	9	81/1274	Y	Box	600 x 500	840	840	1100
A / B-45	45	4 MT	200	385	2.2	9	61/1169	Y	180	620 x 520	770	1260	640
A / B-50	50	4 MT	230	370	3	9	54/1032	Y	200	620 x 520	770	1300	710
BP-50	50	4 MT	230	475	4	9	54/1032	Y	Box	700 x 600	1000	1000	1400
B-60	60	5 MT	260	400	4	12	64/1210	Y	220	700 x 600	660	1250	820
B-70	70	5 MT	260	400	5.5	12	51/966	Y	220	700 x 600	660	1250	840
BP-70	70	5 MT	260	525	7.3	12	51/966	Y	Box	900 x 700	1100	1100	1850

All figures are for flo